

RT09 Conference Speech Recognition System

Dr. Veton Këpuska Arthur Kunkle

LVSR System Goals

- Facilitate re-use by identifying existing solutions for speech recognition tasks
 - HTK (HMM Toolkit)
 - SRILM (SRI Language Modeling Toolkit)
- Use a robust "profile" mechanism to track unique sets of experiment input parameters and organize all models and evaluation results in a single area.
- Ingest data from a variety of sources and account for format and transcription disparities.
- Provide System performance metrics throughout different processing stages for system improvement and research purposes.

HTK System Interface

- Performs major system tasks associated with corpora data preparation, acoustic modeling, Viterbi Search, and lattice rescoring
- Selected for wellorganized baseline.
 Easy to extend for future goals.
- Currently using Version3.4.1


HTK Tool	Purpose
НСору	copy one or more data files to a designated output file, optionally converting the data into a parameterized form
HDMan	used to prepare a pronunciation dictionary from one or more sources.
HLRescore	HLRescore is a general lattice post-processing tool. It reads lattices (for example produced by HVite) and finds the best path.
HVite	HVite is a general-purpose Viterbi word recognizer. It will match a speech file against a network of HMMs and output a transcription for each. When performing N-best recognition a word level lattice containing multiple hypotheses can also be produced
HERest	perform a single re-estimation of the parameters of a set of HMMs, or linear transforms, using an embedded training version of the Baum-Welch algorithm

SRILM System Interface

- Performs major system tasks associated with Language Model Generation
- Currently using Version 1.5.7


LVSR System Overview

- Designed to be an endto-end solution for:
 - Processing labeled speech data from various sources
 - train acoustic and language models
 - perform speech-to-text recognition
- Perl used extensively to abstract HTK calls and provide transcription processing.



Acoustic Model Training

- Perl code manages the workflow between HTK Acoustic Modeling tools.
- Builds phone-based HMM models iteratively:
 - 3-state monophones
 - Context-dependent Triphones
 - Tied-State Triphones using Decision Trees
 - Multi-Gaussian mixture Triphones



Language Model Training Dev. Testing

Train Data : RT0607_TRAIN	Test Data: RT0607_TRAIN				
N-gram Order	5				
Training Parameters	ppl	ppl1	logprob		
kndiscou <mark>nt_</mark> kn-modify-counts-at-end	70.17	74.49	-218926		
kndiscount	55.79	59.03	-207111		
ukndiscount	49.35	30.05	-200800		
ukndiscount_kn-modify-counts-at-end	28.67	30.05	-172828		
default	7.69	7.91	-105041		
interpolate	7.69	7.91	-105041		
wbdiscount	7.56	7.78	-104172		
ndiscount	6.79	6.97	-98620		


Train Data : TIMIT_TRAIN	Test Da	Test Data: TIMIT_TRAIN			
N-gram Order	5				
Training Parameters	ppl	ppl1	logprob		
kndiscount_kn-modify-counts-at-end					
kndiscount			ll la		
ukndiscount	53.75	83.00	-83711		
ukndiscount_kn-modify-counts-at-end	49.02	74.94	-81777		
default	5.99	7.28	-37604		
inter <mark>polate</mark>	5.99	7.28	-37604		
wbdiscount	4.70	5.57	-32536		
ndiscount	4.50	5.30	-31579		

Train Data: RT0607_TRAIN	Test Data: RT0607_TEST				
N-gram Order	5				
Training Parameters	ppl	ppl1	logprob		
kndiscount_kn-modify-counts-at-end	71.37	74.51	-18932		
kndiscount	55.47	57.76	-17814		
ukndiscount	44.84	46.59	-16870		
ukndiscount_kn-modify-counts-at-end	25.14	25.97	-14303		
default	48.83	50.78	-17248		
interpolate	48.83	50.78	-17248		
wbdiscount	44.43	46.16	-16829		
ndiscount	42.34	43.97	-16615		

Train Data : TIMIT_TRAIN Test Data: TIMIT_TEST				
N-gram Order	5	1717		
Training Parameters	ppl	ppl1	logprob	
kndiscount_kn-modify-counts-at-end		1		
kndiscount				
ukndiscount	9.17	11.84	-4735	
ukndiscount_kn-modify-counts-at-end	9.13	11.80	-4727	
default	11.74	15.61	-5264	
interpolate	11.74	15.61	-5264	
wbdiscount	13.65	10.41	-5007	
ndiscount	10.47	13.73	-5019	

Recognizer and Post-Processing

- Utilizes the HTK Recognizer
 HVite to create N-best
 hypothesis lattices for
 evaluation data against an
 "open" grammar network (no
 Language Model)
- Language Models from SRILM then applied to N-best lattices to generate final hypothesis.
- Other factors such as Insertion Penalties, Grammar/Acoustic Scaling Factors applied.
- Results are then displayed using HTK tools or NIST scoring software (SCTK)



RTo9 Evaluation Experiment Setup

- Model training was performed in advance of the evaluation.
- Acoustic Models are built iteratively
- Dictionary based upon CMU Pronunciation Dictionary

Experiment Parameter	Value			
Final Triphone HMM Count	8422			
Dictionary Count	16426			
Language Model Order	3			
Language Model Discounting	Kneser-Ney			
Acoustic Modeling Corpora Used	TIMIT (initial) AMI RT06 RT07			
Language Modeling Corpora Used	RT06 RT07			
MFCC Coefficients	39 (13+13+13)			
Gaussian Mixtures Used	9 (incremented by 3)			

RTog Evaluation Results

- FIT participated in the speech-to-text RTo9 task, which involves generating time-stamped transcriptions of spoken word data.
- Evaluation data is 180 minutes of data collected from ten meetings occurring at two facilities.
- FIT processed Individual Head Microphone data with reference segmentations

Regions	Total	Total	Correct	Substit-	Insertions	Deletions	Word	Sentence
	Time	Words		utions			Error	Error
11852	55883.9	42247	11016	29455	15981	1176	47212	
	N.		(26.1%)	(69.7%)	(37.8%)	(4.2%)	(111.8%)	(50.8%)

LVSR Improvement Goals

- Clearly room for improvement in system performance
- Following areas are planned for additional analysis in the near term:
 - Determine Cause of Excessive Insertion Rate
 - Poor Data Availability for a Large Percentage of Triphone Models
 - Improving User Interface
 - Knowledge Depth of the HTK and SRILM Utilities

Research Projects

Rich Transcription Evaluation

- Baseline Performance note yet complete
- Augment HTK with Wake-Up-Word (WUW)
 Technology (next task)
 - Performance of WUW speech recognition system on whole word recognition task compared against leading commercial speech recognition system (Microsoft's SDK 5.1) showed from 919.67% to 1760.00% and against the leading academic speech recognition system HTK from 1449.75% to 15166.15% improvement (measured as relative error rate reduction)

Research Projects

- Wake-Up-Word (WUW) Speech Recognition (SR)
 - "You talkin' to me?" Key to **spontaneous and natural** human-machine-interaction is to reliably determine if a user is addressing the computer.
 - An WUW is a SR system that is capable of reliably determining if the user is addressing the computer.

Alerting vs. Referential Context

- Alerting:
 - "<u>Computer</u>! Begin PowerPoint Presentation"
- Referential:
 - "I have a <u>computer</u> with dual core 64 bit Intel Processor and 4 GB of RAM."
- On going creative data collection and analysis procedure based on DVD movies to facilitate and refine our understanding of alerting vs. referential context using only prosodic features.

Development

- PowerPoint Commander Voice Activated and Controlled PowerPoint Presentation
- Elevator Simulator



Questions?

